

SAFETY DATA SHEET

1. Identification

Product Identifier: TELONE™ by Teleos Soil Fumigant

Other Means of Identification: 1,3-Dichloropropene

SDS Number 200A-AUS-TCA APVMA Approval No.: 60921/149934

Recommended Use: Plant protection product

Restrictions on Use: For use only by fumigators accredited under the TELONE™ training program.

Importer / Supplier: TriCal Australia Pty Ltd

4 Gidgie Court, Edinburgh, SA 5111, Australia

08 8347 3838

Emergency Phone No.: CHEMTREC (Australia) Phone 1800 862 115 (24/7)

Poisons Information Centre: Phone **13 11 26** from anywhere in Australia

Phone 0800 764 766 in New Zealand

2. Hazard(s) Identification

Physical Hazards: Flammable Liquids Category 3
Health Hazards: Acute Toxicity, inhalation Category 3
Acute Toxicity, dermal Category 3
Acute Toxicity, oral Category 3

Acute Toxicity, oral Category 3
Skin Irritation Category 2
Eye Irritation Category 2A
Skin Sensitization Category 1
Carcinogenicity Category 2

STOT, Single Exposure Category 3 (respiratory)

Aspiration Hazard Category 1
Aquatic, Short-Term (acute) Category 1
Aquatic, Long-Term (chronic) Category 1

Label Elements:

Environmental Hazards:



Flame



Skull



Health



Environment

Signal Word: DANGER

Hazard Statements: Flammable liquid and vapour.

Toxic if swallowed, in contact with skin, or if inhaled.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
Suspected of causing cancer.

Precautionary Statements:

Response

Prevention Obtain, read and follow all safety instructions before use.

Keep away from heat, sparks, open flames, and other ignition sources. No smoking.

Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to

prevent static discharges.

Avoid breathing gas or vapors.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, eye protection, and respiratory protection.

Wash hands and face thoroughly after handling.

Do not eat, drink or smoke when using this product.

Avoid release to the environment, [except for intended use]

Contaminated work clothing should not be allowed out of the workplace.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get

emergency medical help immediately.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical help.

IF ON SKIN: Take off immediately all contaminated clothing and wash it before reuse.

Wash with plenty of water. Get emergency medical help immediately.

IF SWALLOWED: Get emergency medical help immediately. Rinse mouth. Do NOT

induce vomiting.

Specific treatment (see First Aid section of label)

If skin irritation occurs: Get medical help.

If skin irritation or rash occurs: Get medical help.

IF exposed or concerned, get medical advice.

Get medical help if you feel unwell.

Take off contaminated clothing and wash it before reuse.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected

areas with water.

In case of fire: Use fire extinguisher to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store

locked up.

Disposal Dispose of contents/container in accordance with local / regional / national /

international regulations.

Hazard(s) Not Otherwise Classified (HNOC):

lassified (HNOC): For product packaged in cylinders:

Do not spray on an open flame or other ignition source.

In case of leakage, eliminate all ignition sources.

Stop leak, if safe to do so.

In case of fire: Evacuate area. Fight fire remotely due to the risk of cylinder rupture.

3. Composition/Information on Ingredients

Ingredients	Common Name and Synonyms	CAS Number	Concentration by Weight %
1,3-Dichloropropene	TELONE™	542-75-6	100

Product label will reflect nominal active ingredient percentages.

4. First Aid Measures

Description of Necessary First Aid Measures:

Inhalation Move person to fresh air. If person is not breathing, call an emergency responder or

ambulance, then give artificial respiration; if by mouth to mouth, use rescuer protection (pocket mask, etc.). Call a Poisons Information Centre or doctor for treatment advice.

If breathing is difficult, oxygen should be administered by qualified personnel.

Skin Contact Take off immediately all contaminated clothing. Wash skin with soap and plenty of

water for 15-20 minutes. Call a Poisons Information Centre or doctor for treatment advice. Suitable emergency safety shower facility should be immediately available.

Eye Contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a Poisons Information Centre or doctor for treatment advice. Suitable emergency eye wash facility

should be immediately available.

Ingestion Seek medical attention immediately. Do NOT induce vomiting, rinse mouth thoroughly

with water and contact a Poisons Information Centre, or call a doctor at once.

Symptoms Caused by Exposure: Aside from the information found in this Section 4, any additional important symptoms

and effects are described in Section 11: Toxicology Information.

Medical Attention and Special

Notes to physician: Skin contact may aggravate preexisting dermatitis. Maintain adequate ventilation and oxygenation of the patient. May cause asthma-like (reactive

adequate ventilation and oxygenation of the patient. May cause asthma-like (reactive airways) symptoms. Bronchodilators, expectorants, antitussives and corticosteroids may be of help. Respiratory symptoms, including pulmonary oedema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Because rapid absorption may occur through the lungs if aspirated and cause systemic effects, the decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when

considering emptying the stomach. Animal data indicates that this material is a potential skin sensitiser. However, skin sensitization has not been encountered among employees involved in the manufacture of this material. No specific antidote.

Treatment of exposure should be directed at the control of symptoms and the clinical

condition of the patient.

General Advice:

Aerate contaminated clothing in a secure area downwind and away from people. Wash clothing before reuse. Shoes and other leather items which cannot be decontaminated

should be disposed of properly. Call the Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 11 26 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have the Safety Data Sheet (SDS), and if available, the product container or label with you when calling a Poisons Information Centre or doctor, or going for treatment.

First Aid responders should pay attention to self-protection and use recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

5. Fire-Fighting Measures

Suitable Extinguishing Media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire

extinguishers. Foam. General purpose synthetic foams (including AFFF type) or protein foams are preferred, if available. Alcohol resistant foams (ATC type) may function.

Water fog, applied gently may be used as a blanket for fire extinguishment.

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this may not be effective to extinguish fire.

Specific Hazards Arising from the Chemical:

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Hydrogen

chloride. Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Electrically ground and bond all equipment. Flammable mixtures of this product are readily ignited even by static discharge. Vapours are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Flammable mixtures may exist within the vapour space of containers at room temperature. Flammable concentrations of vapour can accumulate at

temperatures above flash point; see Section 9.

Special Protective Equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire

for Firefighters:

fighting clothing (includes firefighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during firefighting operations. If contact is likely, change to full chemical-resistant firefighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

Precautions for Firefighters:

Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water may not be effective in extinguishing fire. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of re-ignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles.

Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream; may spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimise property damage. Water fog, applied gently may be used as a blanket for fire extinguishment.

Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this SDS.

6. Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to section 7, Handling, for additional precautionary measures. Keep personnel out of low areas. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapour to avoid fire or explosion. Vapour explosion hazard. Keep out of sewers. For large spills, warn public of downwind explosion hazard. Check area with combustible gas detector before reentering area. Ground and bond all containers and handling equipment. Eliminate all sources of ignition in vicinity of spill or released vapour to avoid fire or explosion. Use appropriate safety equipment. For personal protection, see Section 8 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

Environmental Precautions:

Ground and bond all containers and handling equipment. Pump with explosion-proof equipment. If available, use foam to smother or suppress. Contain spilled material if possible.

Methods and Materials for Containment and Cleaning Up:

Absorb with materials such as: Clay. Dirt. Sand. Sweep up. Collect in suitable and properly labeled containers.

Large Spills

Small Spills

Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

After Spill Clean-up

Never return spills to original containers for reuse. For waste disposal, see section 13 of the SDS.

7. Handling and Storage

Precautions for Safe Handling:

Keep out of reach of children. Keep away from heat, sparks and flame. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Vapours are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour or mist. Do not swallow. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation. Never use air pressure for transferring product. No smoking, open flames or sources of ignition in handling and storage areas. Containers, even those that have been emptied, can contain vapours. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. See Section 8, Exposure Controls/Personal Protection.

For additional information on equipment bonding and grounding, refer to the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions

Arising out of Static, Lightning, and Stray Currents" or AS/NZS 1020 Control of Undesirable Static Electricity.

Conditions for Safe Storage, Including Incompatibilities:

This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store locked up. Store in a dry place. Do not store near food, foodstuffs, drugs or potable water supplies. Store in original tightly-closed container. Do not store in: Zinc. Aluminum. Aluminum alloys. Magnesium. Magnesium alloys. Eliminate sources of ignition, such as static build-up, heat, spark or flame. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.

Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 500 kg or L of Category 1 Dangerous Goods, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label. Also, avoid contact or contamination of product with incompatible materials listed in Section 10. Store at temperatures not exceeding 55 °C.

8. Exposure Controls and Personal Protection

Occupational Exposure Limits:

SWA Exposure Limits:

Component	CAS No.	TWA (mg/m³)	STEL (mg/m ³)	Skin Notation
1,3-Dichloropropene	542-75-6	4.5	Not established	Can be absorbed via skin

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5-day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equaled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL.

Biological Monitoring: No biological exposure limits noted for the ingredient(s).

Control Banding: Not assigned.

Engineering Controls: No special ventilation requirements are normally necessary for this product during its

intended use outdoors as an agricultural soil fumigant. However, in the event the product is handled indoors, such as in a lab environment, make sure that the work environment remains clean and that vapours and mists are minimised. Good general ventilation (typically 10 air changes per hour) should be used. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain

airborne levels below recommended exposure limits.

Eyebaths or eyewash stations and safety deluge showers or water flushing facilities

should, if practical, be provided near to where this product is being handled

commercially.

Individual Protection Measures: The instructions below are for bulk handling or where regular exposure in an

occupational setting occurs without proper containment systems.

Eye and Face Protection Your eyes must be completely protected from this product by splash-resistant goggles

with face shield. All surrounding skin areas must be covered. Emergency eye wash facilities must also be available in an area close to where this product is being used.

Skin Protection Avoid contact with the skin. Because of the hazardous nature of this product, make

sure that all skin areas are completely covered by impermeable gloves, overalls, hair covering, apron and face shield. Suitable material types include Tyvek®, Saranex®,

and/or Tychem®.

Hand Protection Use gloves chemically resistant to this material. Examples of preferred glove barrier

materials include: Ethyl vinyl alcohol laminate ("EVAL"). Viton. Examples of acceptable glove barrier materials include: Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also account for relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as

well as the instructions/specifications provided by the glove supplier.

Respiratory Protection If engineering controls do not maintain airborne concentrations below recommended

exposure limits (where applicable) or to an acceptable level, an approved respirator must be worn. If sensory irritation is experienced or if there is a significant chance that vapours or mists are likely to build up in the area where this product is being used, use

a full-facepiece air-purifying respirator. It should be fitted with a type A cartridge,

suitable for organic vapours, with a particulate pre-filter.

For emergency or planned entry into unknown concentrations: Any self-contained breathing apparatus that has a full-facepiece and is operated in a pressure-demand or

other positive-pressure mode.

General Hygiene When using, do not eat, drink or smoke. Always observe good personal hygiene Considerations: measures, such as washing after handling the material and before eating, drinking

measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

Relevant Australian Standards: The following Australian Standards will provide general advice regarding safety clothing

and personal protective equipment (PPE):

Respiratory equipment: AS/NZS 1715. Protective Gloves: AS 2161. Occupational Protective Clothing: AS/NZS 4501 set 2008. Industrial Eye Protection: AS1336 and

AS/NZS 1337. Occupational Protective Footwear: AS/NZS2210.

9. Physical and Chemical Properties

Appearance:

Physical State Liquid

Colour Colourless to yellow

Odour Sharp, sweet, penetrating, chloroform-like odour

Odour Threshold No test data available

pH 6.5 1% CIPAC MT 75 (1% aqueous suspension)

Melting Point/Range Not applicable

Freezing Point No test data available Boiling Point (760 mmHg) 107 °C (225 °F)

Flash Point 27 °C (81 °F), closed cup EC Method A9 (equivalent to Pensky-Martens)

Auto-Ignition Temperature 92/69/EEC A15 none below 400 °C

Evaporation Rate

Flammability (solid, gas)

Lower Flammability Limit

Upper Flammability Limit

Vapour Pressure

No test data available

No test data available

No test data available

23 mm Hg @ 20 °C (68 °F)

Vapour Density (air =1) 3.8

Relative Density (water -1) 1.21 at 20 °C (68 °F) / 4 °C Pyknometer

Liquid Density 1.211 g/cm3 at 20 °C (68 °F) Digital density metre Water Solubility Insoluble, but miscible in most organic solvents

Partition Coefficient log Pow: 1.82 to 2.1 (measured)

(n-octanol/water)

Decomposition Temperature Not available

Dynamic Viscosity 0.66 mPa.s at 40 °C (104 °F) Kinematic Viscosity 0.636 mm2/s at 20 °C (68 °F)

Particle Characteristics Not relevant because the product is a liquid.

Other Information:

Explosive Properties No data available
Oxidizing Properties No data available
Volatility Easily evaporates
Molecular Weight 110.97 g/mol

10. Stability and Reactivity

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and

transport.

Chemical Stability: Unstable at elevated temperatures.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions to Avoid: Exposure to elevated temperatures can cause product to decompose. Generation of

gas during decomposition can cause pressure in closed systems. Avoid static

discharge.

Incompatible materials Avoid contact with: Acids. Bases. Oxidisers. Avoid contact with

metals such as: Zinc. Cadmium. Magnesium. Aluminum. Aluminum alloys.

Hazardous Decomposition

Products

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Carbon monoxide. Carbon dioxide. Hydrogen chloride. Toxic gases are released during decomposition. Decomposition products can include trace amounts of: Phosgene.

11. Toxicological Information

Information on Toxicological Effects:

Acute Oral Toxicity LD₅₀: > 110 mg/kg, Rat

Moderate toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Swallowing may result in gastrointestinal irritation.

Acute Dermal Toxicity LD₅₀: 333 mg/kg, Rabbit

Prolonged or widespread skin contact may result in absorption of harmful amounts.

Acute Inhalation Toxicity LC₅₀: > 2.7 to < 3.07 mg/L (595 ppm), Rat, 4-hour, vapour

Prolonged excessive exposure may cause serious adverse effects, even death. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and

lungs. Observations in animals include: Lethargy and incoordination (ataxia).

Skin Corrosion/Irritation Brief contact may cause moderate skin irritation with local redness.

May cause drying and flaking of the skin.

Direct effects on skin - slight to moderate erythema and edema when 0.5 milliliter of the undiluted substance was applied under occlusion to the skin of rabbits for 4 hours.

Serious Eye Damage/Eye

Irritation

May cause severe eye irritation. May cause slight corneal injury. Vapour may cause lacrimation (tears). Vapour may cause eye irritation experienced as mild discomfort

and redness.

Respiratory Sensitization No data available.

Skin Sensitization Animal data indicate that 1,3-Dichloropropene is a potential skin sensitiser (allergic

contact dermatitis - itchy skin, edema, blisters, burning feeling).

Germ Cell Mutagenicity In vitro genetic toxicity studies were negative in some cases and positive in other cases.

Animal genetic toxicity studies were negative.

Carcinogenicity Has been shown to cause cancer in laboratory animals by the oral route. Inhalation

exposure resulted in an increase in normal occurrence of benign lung tumors in male

mice.

International Agency for Research on Cancer (IARC) Monographs.

Overall Evaluation of Carcinogenicity - Group 2B Possibly carcinogenic to

humans.

There is sufficient evidence in experimental animals for the carcinogenicity of

mixed isomers of technical grade.

National Toxicology Program (NTP) Report on Carcinogens (14th Report)

Reasonably Anticipated to be a Human Carcinogen.

Work Health and Safety Regulations (Schedule 10) - Australia

No component in mixture is listed.

Reproductive Toxicity In animal studies, did not interfere with reproduction.

Did not cause birth defects or other effects in the fetus even at doses which caused Teratogenicity

toxic effects in the mother.

Specific Target Organ Toxicity May cause respiratory irritation.

Single Exposure

Skin absorption - considered systemically available via liquid or vapour and can be

neurotoxic following acute dermal exposure.

Specific Target Organ Toxicity

Repeated Exposure

In animals, effects have been reported on the following organs:

Bladder. Nasal tissue. Liver. Lung. Gastrointestinal tract. Respiratory tract.

Blood-forming organs (Bone marrow & Spleen).

Aspiration Hazard May be fatal if swallowed and enters airways.

Information on Possible Routes

of Exposure:

(mainly due to vapours in air) Eyes (by inhalation of vapours) Respiratory Tract

Skin (contact with liquid and vapours) (with potential for aspiration) Ingestion

Early Onset of Symptoms Related to Exposure:

Respiratory, skin, and eye irritation. Headache, dizziness, nausea, chest discomfort,

coughing, breathing difficulty.

Difficulty breathing if substance is aspirated.

Delayed Health Effects

from Exposure:

Allergic contact dermatitis in humans and animals following repeated or prolonged skin

exposure.

Exposure Levels/Health Effects: No data available (see above information on Acute Toxicity for oral, dermal, and

inhalation in animals.

Interactive Effects: No data available.

Other Information: None.

12. Ecological Information

Ecotoxicity:

Material is highly toxic to aquatic organisms on an acute basis (LC₅₀/EC₅₀ between 0.1 Acute Toxicity to Fish

and 1 mg/L in the most sensitive species tested).

LC₅₀: 2.78 mg/L, 96-hour, Oncorhynchus mykiss (rainbow trout)

LC₅₀: 0.87 mg/L, 96-hour, *Cyprinodon variegatus* (sheepshead minnow)

LC_{50:} 3.7 mg/L, 96-hour, *Lepomis macrochirus* (bluegill sunfish)

Acute Toxicity to Aquatic

Invertebrates

EC₅₀: 3.58 mg/L, 48-hour, *Daphnia magna* (water flea) EC₅₀: 0.64 mg/L, 48-hour, *Crassostrea virginica* (eastern oyster) Acute Toxicity to Algae/ EbC₅₀: 14.9 mg/L, 72-Hour, *Pseudokirchneriella subcapitata* (green algae), static test,

Biomass

Aquatic Plants EC₅₀: 2.35 mg/L, 120-Hour, diatom *Navicula* sp., Biomass

EC₅₀: 14.56 mg/L, 14-d, Lemna gibba

Chronic Toxicity to Fish NOEC: 0.0318 mg/L, 33-d, *Pimephales promelas* (fathead minnow), flow-through test,

survival

Chronic Toxicity to Aquatic

Invertebrates

NOEC: 0.0701 mg/L, 21-d, Daphnia magna (water flea), number of offspring

Toxicity to Aboveground Material is moderately toxic to birds on an acute basis (LD50 between 51 and 500

mg/kg).

Organisms Material is practically non-toxic to birds on a dietary basis (LC₅₀ > 5000 ppm).

Oral LD₅₀: 139.8 mg/kg, Colinus virginianus (bobwhite quail), mortality, bodyweight.

Dietary LC₅₀: > 6243 mg/kg, Anas platyrhynchos (mallard duck), diet

Toxicity to Soil-Dwelling

Organisms

LC₅₀: 55.6 mg/kg, 14-d, Eisenia fetida (earthworms)

Persistence and Degradability:

Biodegradability Biodegradation may occur under aerobic conditions (in the presence of oxygen).

10-day Window: Fail

Biodegradation 4.9%

Method: OECD Test Guideline 301D or Equivalent

Theoretical Oxygen Demand 1.281 mg/mg
Biological Oxygen Demand 0.148 mg/mg
Stability in Water (1/2-life) 2.3 to 4.75 days

Photodegradation 7 to 12 hours (atmospheric 1/2-life)

Bioaccumulative Potential No data available for this product. For similar material(s): Bioconcentration potential is

low (BCF < 100 or Log Pow < 3).

Partition Coefficient: n-octanol /

Water (log Kow)

1.82 to 2.1 (measured

Mobility in Soil For similar material(s):

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 44.7 Measured

Other Adverse Effects No other adverse environmental effects (e.g., ozone depletion, photochemical ozone

creation potential, endocrine disruption, global warming potential) are expected.

13. Disposal Considerations

Disposal Methods Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways

or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local Disposal Regulations Special help is available for the disposal of Agricultural Chemicals. The product label

will give general advice regarding disposal of small quantities, and how to cleanse

containers.

For help with the collection of unwanted rural chemicals, contact:

ChemClear 1800 008 182 http://www.chemclear.com.au/

For help with the disposal of empty drums, contact:

DrumMuster http://www.drummuster.com.au/

for contact details for your area.

Waste from Residues / Unused

Products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a

safe manner (see: Disposal Methods).

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not clean drum with caustic or lye. Since emptied containers may retain

product residue, follow label warnings even after container is emptied.

14. Transport Information

Product is a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number 2903

Proper Shipping Name: Pesticide, liquid, toxic, flammable, n.o.s.(1,3-Dichloropropene)

Transport Hazard Class: 6.1 (Toxic)

Subsidiary Risk: 3 (Flammable Liquid)

Packing Group Number:

Environmental Hazards for

Transport Purposes:

1,3-Dichloropropene (acute and chronic aquatic toxicity) - Marine Pollutant

Special Precautions for Users: Packages must be secured against all movement during transport. Keep

markings, labels or placards on the package until cleaned and purged of residue including bulk and non-bulk packages. For cylinders, ensure valve is closed and

safety cap(s) and valve protection are in place prior to transport.

Additional Information: This information is not intended to convey all specific regulatory or operational

requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the

responsibility of the transporting organization to follow all applicable laws,

regulations and rules relating to the transportation of the material.

Hazchem Code: 3WE Hazard Identification Number (HIN) 663/63

15. Regulatory Information

Australian Inventory of Chemical Substances (AICS):

1,3-Dichloropropene is regulated by SUSMP.

1,3-Dichloropropene, CAS 542-75-6 is listed as 1-Propene, 1,3-dichloro- when used as an industrial chemical.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

1,3-Dichloropropene Schedule 7 (see Note:)

Note: Appendix J, Part 2 - Schedule 7 Poisons Requiring Additional Controls on Availability and Use

1,3-Dichloropropene is listed in Appendix J, Part 2.

All poisons included in Appendix J, Part 2 are not to be available except to authorised or licensed persons.

Montreal Protocol on Substances that Deplete the Ozone Layer:

Component not listed.

Stockholm Convention on Persistent Organic Pollutants:

Component not listed.

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade:

Component not listed in Annex III.

New Zealand Inventory (NZIoC):

1,3-Dichloropropene, CAS 542-75-6 is listed.

16. Other information, including date of preparation or last revision

This SDS prepared in accordance with SWA Code of Practice: Preparation of Safety Data Sheets for Hazardous Chemicals, July 2020, amended to reflect GHS 7.

Version 1 Date: December 8, 2025

Revision History:

dd:mm:yyyy Revision Date Format

08/12/2025 Initial version

ABBREVIATIONS:

APVMA	Australian Pesticides and Veterinary Medicines Authority		
CAS	Chemical Abstracts Service		
CHEMTREC	Chemical Transportation Emergency Center		
EbC ₅₀	The concentration of test substance which results in a 50 percent reduction in biomass growth relative to the control within 72 hrs exposure. Regarded as acute endpoint.		
	Half Maximal Effective Concentration - concentration of a material in water, a single dose which is		
EC ₅₀	expected to cause a biological effect on 50% of a group of test species.		
IMDG	International Maritime Dangerous Goods		
LC ₅₀	Lethal Concentration - median dose at which 50% of test animals die from inhalation		
LD ₅₀	Lethal Dose - median dose at which 50% test animals die from oral or dermal exposure		
NOEC	No Observed Effect Concentration		
NTP	National Toxicology Program		
ppm	part(s) per million		
STOT	Specific Target Organ Toxicity		
TWA	Time Weighted Average airborne concentration for a worker in an 8-hour day		

WARRANTY

Notice: The information above is believed to be accurate and represents the best information currently available to us. Seller warrants that this product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with directions under normal conditions of use, but neither this warranty nor any other warranty of merchantability or fitness for a particular purpose, express or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to seller, and buyer assumes the risk of any such use. In no way shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages, howsoever arising, even if the company has been advised of the possibility of such damages.

TELONE™ and Teleos Ag Solutions™ are registered trademarks of Teleos Ag Solutions, Inc.
TELONE™ by Teleos Soil Fumigant is an APVMA approved pesticide. Always read and follow label directions.